



ELECTRIC PUSH-PUSH CONTROL-12V (D3M)	
Rated voltage	12 VDC
Rated current	3 A
Rated power	45 W
Permitted working voltage	+/-10% Nominal
Max ambient temperature	+40°C
Max oil temperature	+80°C
Operation time	S1 (100%)
Protection degree	IP65
Insulation degree	H
Standard connector	DIN 43650

STANDARD WORKING CONDITION	
Max. Inlet Flow	55 l/min
Max. Input Pressure	350 bar
Max. back pr. on Tank line	20 bar
Operating temperature range	-20/+80°C
Kinematic Viscosity Range	10-300 cst
Max. Contamination level	9 (NAS 1638) - 20/18/15 (ISO 4406:1999)
Recommended Filtration level	b10 >75 (ISO 16889 : 2008)
PORT DIMENSIONS:	
Tank Port T	1/2"-BSP
Inlet Port P	1/2"-BSP
Working Ports A & B	1/2"-BSP

Description: HC-D3M/8



Group: D3M		Scale	
Approv.	Date	Schema Code	
		90286	
Designer: MS	Date: 17/06/2014	CODE: I06959	Mod.: 0

0 17/06/2014 EMISSIONE  
 Documento riservato a termini di Legge con divieto di riproduzione o di renderlo comunque noto a terzi senza esplicita autorizzazione